pH Electrode, ORP Electrode

ER1, ER2, ER3, ER4, ER5, ER6, ER7, ER8, ER9, ER10

pH ELECTRODE - ER1

0-14 pH

5 -60°C

Plastic Type - For General Lab Use Application

pH ELECTRODE - ER6

2-12 pH

5 -90°C

Glass type, Ceramic - Junction - For Low Ionic Strength Measurement Solution, like high pure water

pH ELECTRODE - ER2

0-14 pH

5 -60°C

Plastic Type - For Waste Solution, not suitable for Strong acid / Alkaline Solution Measurement

ORP ELECTRODE - ER7

± 1000mV

5 -60°C

Plastic Type - For General Application of ORP (Redox).Milivolt range(Redox)±1000mV, Temp. range: 5° to 60°C

pH ELECTRODE - ER3

0-14 pH

5 -60°C

Plastic Type - For High/Low Ionic Concentration sample like rain water, Sea water & Drinking water

ORP ELECTRODE - ER8

± 1000mV

5 -90°C

Glass Type - For High temperature Application of ORP (Redox). Milivolt range(Redox)±1000mV, Temp. range: 5° to 90°C

pH ELECTRODE - ER4

2-12 pH

5 -60°C

Plastic Type - Flat Surface for Food, Cheese, Paper, Skin, Meat, Butter, etc...

DO ELECTRODE - ER9

0 - 20ppm

0 -50°C

DO electrodes measure the concentration of dissolved oxygen in water or other liquids using an electrochemical sensor.



pH ELECTRODE - ER5

0-14 pH

5 -90°C

Glass Type : Liquid JunctionType - Ceramic or Strong Acid, Alkaline, Organic Solution Measurement



pH ELECTRODE - ER10

0 - 14 pH

05 -70°C

Glass type, Refillable(KCl filled)
Ceramic Junction - For General Lab Use