



SALIENT FEATURES

- ◆ 4.3" Touch Screen display
- ◆ SS304 Connectors for circulation and drainage.
- ◆ SS304 stainless steel table plate and inner liner.
- ◆ Built-in, drain valve.
- ◆ Automatically drains excess water overflow
- ◆ Heatless circulation pumps.
- ◆ Low noise.
- ◆ Transparent tube to show current Water level
- ◆ Easy lifting and moving 2 side handles

Recirculating Water Chiller used for Rotary evaporator, Glass reactor, Viscometer, Rheometer, Electrophoresis, Abbe refractometer, Ultrasonic Homogenizer, etc.

Recirculating Water Chiller

RWC320

HSN Code : 84189100



E - Catalogue

SPECIFICATIONS

MODEL	RWC320
Make	LABMAN
Bath capacity	3.5 L
Pump Lift	2 m
Pump Flow	8 L/min
Total power	1200W
Inner Material	SS304
Circulation & Drainage Port	SS304
Display	4.3" TFT touch screen display
Temperature Control System	PID
Water Filling Hole	35mm
Ambient Temperature	10°C~25°C
Temperature control range	-20°C to 100°C
Temperature Resolution	0.01°C
Temperature Constancy	0.1°C
Power supply	220V/50Hz
Inter Size (LxWxH mm)	180 x 170 x 130mm
Instrument Dimension (LxWxH)	440 x 300 x 510mm
Packing Dimension (LxWxH)	520 x 370 x 600mm
Gross Weight	30kg

★ Specifications are subject to change without notice.

STANDARD ACCESSORIES : Main Instrument, Thermal sleeve -2pcs. Drain pipe (30cm), Fuse, Powercord, Instruction Manual, Test Certificate.